Translation

(1) EC-Type Examination Certificate

(2) Equipment and protective systems intended for use in potentially explosive atmospheres, **Directive 94/9/EC**



(4) for the equipment: Measuring Transmitter VISY-Reed

(5) of the manufacturer: FAFNIR GmbH

(6) Address: Bahrenfelder Str. 19

22765 Hamburg

Germany

Order number: 8000374581

Date of issue: 2009-09-10

(7) This equipment or protective system and any acceptable variation thereto are specified in the schedule to this certificate and the documents therein referred to.

- (8) The TÜV NORD CERT GmbH, notified body No. 0044 in accordance with Article 9 of the Council Directive of the EC of March 23, 1994 (94/9/EC), certifies that this equipment or protective system has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment and protective systems intended for use in potentially explosive atmospheres given in Annex II to the Directive. The examination and test results are recorded in the confidential report No. 09203374581.
- (9) Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

EN 60 079-0:2006 EN 60079-11:2007 EN 60079-26:2007

- (10) If the sign "X" is placed after the certificate number, it indicates that the equipment or protective system is subject to special conditions for safe use specified in the schedule to this certificate.
- (11) This EC-type examination certificate relates only to the design, examination and tests of the specified equipment in accordance to the Directive 94/9/EC. Further requirements of the Directive apply to the manufacturing process and supply of this equipment. These are not covered by this certificate.
- (12) The marking of the equipment or protective system must include the following:

⟨Ex⟩ II 1 Ga Ex ia IIC T4 resp. II 2 Gb Ex ia IIC T4...T6

TÜV NORD CERT GmbH, Langemarckstraße 20, 45141 Essen, accredited by the central office of the countries for safety engineering (ZLS), Ident. Nr. 0044, legal successor of the TÜV NORD CERT GmbH & Co. KG Ident. Nr. 0032

The head of the certification body

Schwedt

Hanover office, Am TÜV 1, 30519 Hannover, Fon +49 (0)511 986 1455, Fax +49 (0)511 986 1590

TUV NORD



(13) SCHEDULE

(14) EC-Type Examination Certificate No. TÜV 09 ATEX 374581

(15) Description of equipment

The measuring transmitter type VISY-Reed ... is used for liquid detection in hazardous explosive areas.

The permissible ambient temperature ranges in dependence of the temperature class have to be taken from the following tables:

Use as Kategorie 1 apparatus

Temperature class	Ambient temperature range
T4	-20 °C to +60 °C

The process pressure of the media has to be from 0.8 bar to 1.1 when potentially explosive mist air mixtures exit. If no potential explosive mixtures exist, the device may also be operated outside of this stated range according to the specification of the manufacturer.

Use as Kategorie 2 apparatus

Temperature class	Ambient temperature range
T4	-40 °C to +75 °C
T5	-40 °C to +65 °C
T6	-40 °C to +50 °C

Electrical data

Signal- and powercircuit (terminals +; A; B; -)

in type of protection "Intrinsic Safety" Ex ia IIC/IIB only for the connection to a certified intrinsically safe circuit

Maximum values: $U_i = 15 \text{ V}$

 $l_i = 60 \text{ mA}$

 $P_i = 100 \text{ mW}$

 $L_i = 120 \mu H$

 $C_i = 10 \text{ nF}$

- (16) Test documents are listed in the test report No. 09203374581.
- (17) Special conditions for safe use

none

(18) Essential Health and Safety Requirements

no additional ones



Translation 1. SUPPLEMENT

to Certificate No.

TÜV 09 ATEX 374581

Equipment:

Environmental Sensor for Leakage Detection type

VISY-Reed ...

Manufacturer:

FAFNIR GmbH

Address:

Bahrenfelder Straße 19

22765 Hamburg

Germany

Order number:

8000441810

Date of issue:

2015-01-14

Amendments:

In the future, the environmental sensors type VISY-Reed ... may also be manufactured according to the test documents listed in the test report.

The amendments concern the ambient temperature range as well as the "Electrical Data".

Also the equipment was assessed according to the latest standards.

The permissible ambient temperature ranges in dependence of the temperature class have to be taken from the following tables:

Use as category 1 apparatus

Temperature class	Ambient temperature range
T6	-20 °C to +50 °C
T5 to T1	-20 °C to +60 °C

The process pressure of the media has to be from 0.8 bar to 1.1 bar when potentially explosive mist air exist. If no potential explosive mixtures exist, the devices may also be operated outside of this stated range according to the specification of the manufacturer.

Use as category 2 apparatus

Temperature class	Ambient temperature range
Т6	-40 °C to +50 °C
T5	-40 °C to +65 °C
T4 to T1	-40 °C to +85 °C

P17-F-006 06-06 page 1/2



1. Supplement to Certificate No. TÜV 09 ATEX 374581

Electrical Data

Signal and supply circuit (terminals +, A, B, -)

in type of protection "Intrinsic Safety" Ex ia IIC/IIB only for the connection to a certified intrinsically safe circuit

Maximum values: $U_i = 15 \text{ V}$

 $I_i = 60 \text{ mA}$

 $P_i = 100 \text{ mW}$

 $L_i = 100 \mu H$

 $C_i = 10 \text{ nF}$

The device will then be labelled as follows:

 $\langle \epsilon_x \rangle$

II 1 G Ex ia IIC T6...T5 Ga

resp.

II 2 G Ex ia IIC T6...T4 Gb

All other data apply unchanged for this supplement.

The equipment meets inclusive of this supplement the requirements of these standards:

EN 60079-0:2012

EN 60079-11:2012

EN 60079-26:2007

- (16) Test documents are listed in the test report No. 15 203 152254.
- (17) Special conditions for safe use

none

(18) Essential Health and Safety Requirements

no additional ones

TÜV NORD CERT GmbH, Langemarckstraße 20, 45141 Essen, notified by the central office of the countries for safety engineering (ZLS), Ident. Nr. 0044, legal successor of the TÜV NORD CERT GmbH & Co. KG Ident. Nr. 0032

The head of the notified body

Schwedt

Hanover office, Am TÜV 1, 30519 Hannover, Fon +49 (0)511 986 1455, Fax +49 (0)511 986 1590